

RP-DN

ring downlight

order sequence information

RP-DN-

EXAMPLE **1** RP-DN- 48 **2** 3000 **3** WHT **4** SPC

PROJECT: _____ TYPE: _____

DATE: _____

1	CAT NO.	DESCRIPTION	DELIVERED LUMENS
	RP-DN-24	24" diameter,	2,516 lumens, 35 watts
	RP-DN-30	30" diameter,	3,362 lumens, 40 watts
	RP-DN-36	36" diameter,	3,362 lumens, 50 watts
	RP-DN-48	48" diameter,	5,043 lumens, 70 watts
	RP-DN-60	60" diameter,	7,565 lumens, 100 watts
	RP-DN-72	72" diameter,	7,565 lumens, 100 watts
	RP-DN-84	84" diameter,	9,246 lumens, 125 watts
	RP-DN-96	96" diameter,	10,086 lumens, 135 watts
	RP-DN-108	108" diameter,	10,927 lumens, 150 watts
	RP-DN-144	144" diameter,	15,129 lumens, 220 watts

CAT NO.	DESCRIPTION	DELIVERED LUMENS
RP-DN-24-HO	24" diameter,	5,032 lumens, 70 watts
RP-DN-30-HO	30" diameter,	5,032 lumens, 90 watts
RP-DN-36-HO	36" diameter,	6,724 lumens, 90 watts
RP-DN-48-HO	48" diameter,	10,086 lumens, 140 watts
RP-DN-60-HO	60" diameter,	15,129 lumens, 220 watts
RP-DN-72-HO	72" diameter,	15,129 lumens, 220 watts
RP-DN-84-HO	84" diameter,	20,172 lumens, 250 watts
RP-DN-96-HO	96" diameter,	20,172 lumens, 270 watts
RP-DN-108-HO	108" diameter,	21,853 lumens, 300 watts
RP-DN-144-HO	144" diameter,	30,258 lumens, 440 watts

• LEDs are Luxeon XF-3535L. Drivers are Class 2, 120-277 volt, and include two wire 0-10v dimming, 1-100%.
 * Other sizes available. Contact factory for details.

2	LED COLOR TEMP
	2700 2700°K CRI >80
	3000 3000°K CRI >80
	3500 3500°K CRI >80
	4000 4000°K CRI >80

• **RGB Options** RGB and RGB + white (2700K) LED options are available. Hand held remote included and phone Apps are available. Decoder options for connecting to a DMX system.

3	COLOR
	WHT Matte white powder coat
	GRY Matte gray (RAL7035) powder coat
	ASL Anodized silver powder coat
	RAL Specify 4 digit RAL color number

4	MOUNTING
	MCC Multiple suspension cables attach to a center canopy. • 24, 36, 48, 60, 72 and 84 inch diameter rings have 3 cables. Larger sizes have six cables.
	SPC Single point canopies (with one feed canopy) • 24, 36, 48, 60, 72 and 84 inch diameter rings have 3 sets of canopy/cables. Larger sizes have six canopy/cable sets. • Canopies are matte white. 5 wire SJT cords are white. Cables are adjustable. Standard length is 100".
	CMT Ceiling mount



Housing: Formed aluminum.

Lens: High transmissive frosted acrylic.

Certification: UL listed.

Warranty: 5 year limited warranty.

- 24", 30", 36", 48", and 60" fixtures ship in one piece.
- 72", 84", 96", 108" and 144" rings ship in three pieces for field assembly.

