

RPM-UP-DN

mini profile ring pendant uplight + downlight

order sequence information

RPM-UP-DN-

1

2

3

4

EXAMPLE RPM-UP-DN-48 3500 ASL SPC

PROJECT: _____

TYPE: _____

DATE: _____

1 CAT NO. DESCRIPTION

RPM-UP-DN-24	24" diameter, 4,520 lumens,	35 watts
RPM-UP-DN-36	36" diameter, 6,040 lumens,	45 watts
RPM-UP-DN-48	48" diameter, 9,060 lumens,	70 watts
RPM-UP-DN-60	60" diameter, 10,640 lumens,	89 watts
RPM-DN-72	72" diameter, 13,590 lumens,	110 watts
RPM-DN-84	84" diameter, 16,610 lumens,	125 watts

* LEDs are Luxeon XF-3535L. Drivers are Class 2, 120-277 volt, and include two wire 0-10v dimming, 1-100%.

- Drivers can be programmed to a lower lumen output.

2 LED COLOR TEMP

2700 2700°K CRI >80

3000 3000°K CRI >80

3500 3500°K CRI >80

4000 4000°K CRI >80

- **RGB Options** RGB and RGB + white (2700K) LED options are available. Hand held remote included and phone Apps are available. Decoder options for connecting to a DMX system.

3 COLOR

WHT Matte white powder coat

GRY Matte gray (RAL7035) powder coat

ASL Anodized silver powder coat

RAL Specify 4 digit RAL color number

4 MOUNTING

MCC Multiple suspension cables attach to a center canopy.
 • 24, 36, 48, 60, 72 and 84 inch diameter rings have 3 cables. Larger sizes have six cables.

SPC Single point canopies (with one feed canopy)
 • 24, 36, 48, 60, 72 and 84 inch diameter rings have 3 sets of canopy/cables. Larger sizes have six canopy/cable sets.

- Canopies are matte white. 3 wire SJT cords are white. Cables are adjustable. Standard length is 100".



Housing: Formed aluminum.

Lens: High transmissive frosted acrylic.

Certification: UL listed.

Warranty: 5 year limited warranty.

- 24", 36" 48" and 60" fixtures ship in one piece.

